Proxima Ultralight LS2 Projector
Technical and Functional Specifications

Native Resolution	• SVGA (800 x 600)
Resolution Supported	• XGA (1024 x 768), SVGA (800 x 600), VGA (640 x 480), Mac16
Brightness	• 1200 ANSI lumens
Brightness Uniformity	• 90%
Contrast Ratio	• 250:1
Computer Compatibility	• IBM PC or compatibles Apple Macintosh
Video Compatibility	• NTSC, NTSC 4.43, PAL, SECAM, PAL-M, PAL-N
Display Technology	• 0.9 inch TFT LCD x 3
Number of Colors	• 16.7 million colors
Input Sources	• 1 computer, 1 video, 1 S-video, 2 audio
Output	• 1 audio line out, 1 monitor out
H-Sync Range	• 15 - 80 kHz
V-Sync Range	• 50 - 100 Hz
Bandwidth	• 135 MHz
Horizontal Resolution (TV Lines)	• 750 TV lines
Keystone Correction (Optical)	• 10° fixed
Keystone Correction (Digital)	• ±12° adjustable
Projection Lens	• F1.7 - 2.0, focal length 33.2 - 43.1 mm
Projection Distance	• 4.6 ft. to 35.4 ft. (1.4 m to 10.8 m)
Zoom	• 1.3:1 motorized zoom
Aspect Ratio	• 4:3
Image Size	• 2.4 ft. to 24.6 ft. (0.7 m to 7.5 m)
Projection Method	• front/rear, desktop/ceiling
Audio	• 1 watt mono
Remote Control	• Full function remote with mouse control and laser pointer
Lamp	• 150-watt UHP
Dimensions	• 9.4 in. W x 12.7 in. L x 4.1 in. H • 23.9 cm W x 32.3 cm L x 10.3 cm H
Weight	• 8.6 lbs. (3.9 kg)
Power Consumption	• 240 watts
Power Requirements	• 100V - 240V AC (auto voltage)
Operating Temperature	• 41° - 95° F (5° - 35° C)
On-Screen Languages	• English, German, Italian, French, Spanish, Japanese
Audible Noise	• 42 dB
Approvals	• FCC Class A, UL, cUL
Warranty	• Two years on parts and labor (excluding lamp)

Copyright © 1997-2004 InFocus Corporation.
All Rights Reserved.